ARU Joinery

The "Aru 68 CLASSIC IN" window with the bevelled edged sash and frame (rustical profile) is a suitable solution for buildings with a more classical architecture using a double glazed unit. The choice of timber includes knotted and knot free pine, finger jointed Pine, Meranti Oak.

Aru 68 CLASSIC IN

A three-layered deep-impregnated window, the frame is protected with an aluminium glazing bead. The Georgian style bars also have a rustical profile. There's an option of using concealed hinges. Available with a choice of handles.

Aru 68 CLASSIC IN

INWARD OPENING, TILT AND TURN
VACUUM DEEP-IMPREGNATED
WOODEN WINDOW

PROFILE IV68

Jamb: 68 x 68 mm

Frame: 68 x 68 mm

Inside groove for windowcill, outside for aluminium cill

Aluminium slat on the lower part of the frame

FURNITUR

Fittings: ROTO NT

Handle: ROTO, HOPPE

GLASS

24 mm double or triple glazed units (U ≥ 1,1)

Glazing from the inside with wooden glasing bead

Fastened with hidden nails, sealed with silicone

SEAL

2-chamber seal surrounding middle frame rebate

FINISHING

with water-based paint or stain

Handle positions

tilt

microventilation

turn

closed

GLAZING BAR OPTIONS

1. Penetrating bars 50 mm

2. Taped bars Norwegian style

3. Taped bars Georgian style

4. Bars inside the glazing

OPENING:

Inside view

F - FIXED

2x or 3x glazing in the frame. Aluminium slat on the lower part of the frame

min measures 330 x 330 mm

DK - TILT AND TURN (LEFT / RIGHT)

min max L=400...1710 mm   H=408...2527 mm, weight max 130 kg

**D - SIDEHUNG (LEFT / RIGHT)**

min max L=400...1710 mm   H=408...2527 mm, weight max 130 kg

KIPP - TOPHUNG (Handle above)

min max L=330...2510 mm   H=350...1927 mm, weight max 80 kg

NB! Maximum and minimum dimensions and opening possibilities also depend on the apect ratio.
Please ask our specialists for additional information.

Round-headed window